CSF-100 Safety Window Film

purlfrost window film

Tested and certificated to British and EU standards, our 100 micron clear safety film is used as a minimum specification for safety film and is usually adequate for institutional buildings and workplaces concerned to upgrade glass for safety in the context of personal impact.

It is also suitable for residential applications.

BRITISH and EU STANDARDS CERTIFICATION: BS 6206 (6 and 4mm glass): B BS EN 12600 (6 and 4mm glass): 2B2

PERFORMANCES

U.V Transmission	5 %
Visible Light Reflection	11 %
Visible Light Transmission	85 %
Total Solar Energy Rejected	19 %
Solar Reflection	9 %
Solar Absorption	14 %
Solar Transmission	77 %
Glare Reduction	N/A
"g" Value (solar heat gain coef.)	0.83%
"u" Value (EN673W/m².°K)	5.70
Emissivity	0.89
Scratch Resistant Coating	
SUITABILITY	
Clear Single Pane	\checkmark
Tinted Single Pane	\checkmark
Clear Double Pane	\checkmark
Tinted Double Pane	\checkmark
Low-E Clear Double Pane	\checkmark
Clear Laminated Single Pane	\checkmark
Clear Double Laminated Glass	\checkmark
APPLICATION	
INTERNAL	\checkmark
EXTERNAL	Х
WARRANTY: 10 YEARS against	
Peeling	\checkmark
Cracking	1
Demetallization	\checkmark

